Batteries/Accumulators

Date:26.10.2026

Article number: 104 002 - for critical LiPo batteries

www.thermodyne.de
info@thermodyne.de

Thermodyne®
VERPACKUNGSSYSTEME

Table of content

Information 3
Measurements 3
Colors 3

Information

Plastic container with UN approval from BAM (Federal Institute for Materials Research) for the transport of hazardous goods of packing group II and III such as NiCd and defect Li-Ion batteries (P908) according to UN2795 and UN3480 for maximum battery size of 272 x 195 x 135 [mm] and maximum weight of 15kg. The containers also meet ATA300 Cat 1 specification (280 drop tests). Containers in custom color, custom embossing and custom foam insert can be made to order.

Measurements

Interior (l x w x h (base + lid)) [mm]:
272 x 195 x 135

Exterior (l x w x h (base + lid)) [mm]:
354 x 276 x 240 (135 + 0)

Colors

RAL: similar to 9011, black

RAL: similar to 6014, army green

RAL: similar to 9010, white

RAL: similar to 9007, silver grey

RAL: similar to 1021, yellow

RAL: similar to 2004, orange

RAL: similar to 2002, red

RAL: similar to 5002, blue

RAL: similar to 7016, dark grey

RAL: similar to 1002, desert tan

Contact

Date:26.10.2026

Thermodyne GmbH

Nordstr. 15
49086 Osnabrück
Dr.-Ing. Daniel Bätzel

+49 (0) 541 / 181 4997-95
www.thermodyne.de
info@thermodyne.de